



Light guide adaptor 光導互換接頭

Customer use another brand light guide, can be convert as our light guide adaptor, more save money to purchase new.
使用其他公司光導時，應配合本公司所制的互換接頭，可節省重新購買費用。

Model 型號	Applications 用途
Standard diagram LR-1520HSP 標準接頭LR-1520HSP	For all HAYASHI light guide 可用於HAYASHI所有的光導
Exchange light guide adaptor MLC-1517 光導互換接頭MLC-1517	Fixed for company "M" light guide join with MLC-1517 本公司光源與M公司光導相接加用MLC-1517
Exchange light guide adaptor HLC-1511 光導互換接頭HLC-1511	Fixed for company "H" light guide join with HLC-1511 本公司光源與M公司光導相接加用HLC-1511
Exchange adaptor MLR-1537 互換光源接頭MLR-1537	Fixed for company "M" light guide join with MLR-1537 本公司光源與M公司光導相接加用MLR-1537
Exchange adaptor HLR-1531 互換光源接頭HLR-1531	Fixed for company "H" light guide join with HLR-1531 本公司光源與H公司光導相接換用HLR-1531
Exchange adaptor SLR-1330 互換光源接頭SLR-1330	Fixed for company "S" light guide join with SLR-1330 本公司光源與S公司光導相接換用SLR-1330

Remark : Any shape and style light guide adaptor are available.
備註：設有不同形狀及款式的光導互換接頭，以供選擇。

Various kinds of connecting adaptor 各種附件

Model 型號	Applications 用途
Light guide connecting adaptor 光導連接套管 LC-1508	Used when connecting two light guides for extension. Results in 1/2 value of the original lamp intensity. (Adaptable light guides) 用於2根光導相接延長使用時 光亮減為1/2
Condenser lens attachment 集光透鏡固定套管 SK-16	Used when fixing the condenser lens tightly to the light guide by screws. (Adaptable condenser lens). SH-F16, SH-F30 用於將集光透鏡固定在光導上時。 所使用透鏡 SH-F16、SH-F30
Light guide arm attachment 光導固定架 A-14-□	Used when fixing the ring type light guide. 用於分支光導的固定標準型 (A-14-3)要有
Light guide arm attachment 光導固定架 A-20-□	Used when fixing the ring type light guide. 用於環狀光導的固定
Hexagon diffusion fixer tube lens 六角型漫射筒鏡 KA-6	六角型漫射筒鏡的目的為使光源所射出的光的均勻部分通過漫射而得到均勻的照射光。Special for even lighting Standard 標準型(A-20-3)

Shutter Unit (Options) 開閉器單元(顧客自選)

Model 型號	Applications 用途	Operation power 驅動用電源
USW-2E24V	DC24V Rotary solenoid DC24V旋轉式電磁線圈方式	DC24V 0.5AOver DC24V 0.5A以上
SU-2E12V	DC12V Rotary solenoid (with mounting bracket) DC12V旋轉式電磁線圈方式(帶有安裝用的角鐵)	DC12V 1AOver DC12V 1A以上
SU-2E24V	DC24V Rotary solenoid (with mounting bracket) DC24V旋轉式電磁線圈方式(帶有安裝用的角鐵)	DC24V 0.5AOver DC24V 0.5A以上

※ External power (12V/24V) for shutter unit. 驅動開閉器用的電源(12V / 24V)是由外部提供的。
※ Internal power used in LA-150TX with SU-2E-12V 在LA-150TX 選擇SU-2E12V時驅動用電源為內藏。

Power component specification 電磁線圈規格	Specifications 規格
Voltage / Watt 電壓/瓦特	DC24V / 0.25A
Shutter unit power circuit 開閉器用電源回路	Power Component fixed under open or close with rotary solenoid 電磁線圈用電源零件只在選定開閉器時才被裝入。

※ Shutter open or close under non power setting is subject to customer choose before delivery
不按電源時的開閉器的板板狀態的「時常開的狀態」:光照射、「時常閉的狀態」:遮光，是在出廠時由顧客指定進行調整。

Filters 濾片



Filter type number 型號	Filter type number 類型	Adaptable lens/light guide 所適用的鏡片
LB-80 22.5mm LA-120 22.5mm Y-48 22.5mm G-533 22.5mm R-60 22.5mm KF-20 22.5mm PL-20 22.5mm	color temp. conversion filter (light blue) 改變色溫濾色片(淺藍色) color temp. conversion filter (Umber) 改變色溫濾色片(棕色) sharp cut filter (yellow) 銳截止濾色片(黃色) green filter 綠濾色片 sharp cut filter (red) 銳截止濾色片(紅色) diffusion filter 漫射濾片 polarizer 偏振光濾片	SH-F16, SH-F30, SHZ-1, SHZ-2 Lamp House inside fixed available 可裝在SH-F30, SHZ-1, SHZ-2 光源插孔內側上
LB-80 30.5mm LA-120 30.5mm Y-48 30.5mm G-533 30.5mm R-60 30.5mm KF-30 30.5mm PL-30 30.5mm	color temp. conversion filter (light blue) 改變色溫濾色片(淺藍色) color temp. conversion filter (Umber) 改變色溫濾色片(棕色) sharp cut filter (yellow) 銳截止濾色片(黃色) green filter 綠濾色片 sharp cut filter (red) 銳截止濾色片(紅色) diffusion filter 漫射濾片 polarizer 偏振光濾片	Fixed available SH-F42、SHZ-F120 Spot ACE (SPA-10 series) 可裝在SH-F42、SHZ-F120上 點光源高手 (SPA-10系列)
KF-18R KF-31R KF-50R KF-55R KF-61R PL-18R PL-31R PL-50R PL-55R PL-61R	diffusion filter 漫射濾片 diffusion filter 漫射濾片 diffusion filter 漫射濾片 diffusion filter 漫射濾片 diffusion filter 漫射濾片 polarizer 偏振光濾片 polarizer 偏振光濾片 polarizer 偏振光濾片 polarizer 偏振光濾片 polarizer 偏振光濾片	Φ18 ring light guide 適用於Φ18環形光導 Φ31 ring light guide 適用於Φ31環形光導 Φ50 ring light guide 適用於Φ50環形光導 Φ55 ring light guide 適用於Φ55環形光導 Φ61 ring light guide 適用於Φ61環形光導 Φ18 ring light guide 適用於Φ18環形光導 Φ31 ring light guide 適用於Φ31環形光導 Φ50 ring light guide 適用於Φ50環形光導 Φ55 ring light guide 適用於Φ55環形光導 Φ61 ring light guide 適用於Φ61環形光導

※ color filters (Y.G.R.) for ring light guides are also available upon customer's request.
※ 環形用彩色濾片(Y·G·R)為特制。

Color Filter Characteristics 濾片的特性

- A color filter can be used to make a subject more prominent against the background by absorbing one specific color. It is also used for control of image contrast.
彩色濾片使照射光帶有顏色，強調了被照物，更易判別。同時增加演出效果。
- A diffusion filter is used to change the original light into soft one by diffusing high intensity light from the optical Fiber.
彩色濾片使照射光帶有顏色，強調了被照物，更易判別。同時增加演出效果。
- A polarizer is used to prevent diffused reflection. Accordingly, effective.
偏振光濾片可用於防止亂反射，以得有效的照明。

